

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL
- **Product group:**
STROMIT WATERPROOFING APPLICATIONS
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** Suitable for industrial use
- **Application of the substance / the mixture** Insulation product
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
- **WERIMIT**
- OSB 2. Kısım 24. Cad.No:18 Döşemealtı
- Antalya
- TURKEY
-
- Phone: + 90 444 1 290
- **Further information obtainable from:** KGR - Kimyasal Güvenlik Riskleri Dan. Hiz. ve Tic. LTD. ŞTİ.
- **1.4 Emergency telephone number:** +90 444 1 290 (On weekdays, during opening times)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
1,2-benzisothiazol-3(2H)-one
- **Hazard statements**
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one ⚠ Acute Tox. 2, H330; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	<0.01%
CAS: 55965-84-9 Index number: 613-167-00-5	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.01%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Do not give something by mouth to the affected person.
Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately remove any clothing soiled with the product.
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

(Contd. on page 3)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Remove contact lenses.
- **After swallowing:**
Rinse out mouth with plenty of water.
Never give to the unconscious victim anything by mouth.
A person vomiting while laying on their back should be turned onto their side.
Do not induce vomiting; call for medical help immediately.
A person vomiting while laying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During fire conditions, harmful gases are produced.
Formation of toxic gases is possible during heating or in case of fire.
Do not inhale combustion products.
In case of fire, the following can be released:
Carbon monoxide (CO)
Carbon dioxides (CO₂)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Do not inhale combustion products.
If there is a safe way to remove the containers away from the fire area, do it.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Remove persons from danger area.
Ensure adequate ventilation
Do not breathe vapours.
Prevent leakages by avoiding any personnel risk if possible.
Avoid contact with eyes, skin and cloths
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Send for recovery or disposal in suitable receptacles.

(Contd. on page 4)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 3)

6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

- No special precautions are necessary if used correctly.
- Do not inhale vapors.
- Keep away from heat and direct sunlight.
- Ensure good ventilation/exhaustion at the workplace.
- Store in cool, dry place in tightly closed receptacles.
- Keep receptacles tightly sealed.
- Information about fire - and explosion protection:** No special measures required.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:

- Store in a cool location.
- Store only in the original receptacle.
- Information about storage in one common storage facility:**
- Do not store together with heat sources, open flame or ignition sources.
- Do not store together with incompatible materials.
- Store away from food material and animal feed.

Further information about storage conditions:

- Store receptacle in a well ventilated area.
- Protect from heat and direct sunlight.
- Store in cool, dry conditions in well sealed receptacles.
- Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:

- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls
Appropriate engineering controls

- Provide good ventilation.
- No further data; see section 7.

Individual protection measures, such as personal protective equipment
General protective and hygienic measures:

- Wash hands before breaks and at the end of work.
- Do not eat, drink, smoke or sniff while working.
- Keep away from foodstuffs, beverages and feed.
- Avoid contact with the eyes and skin.
- Ensure that eye wash stations are available at the work place.
- Provide good ventilation.
- Immediately remove all soiled and contaminated clothing

Respiratory protection:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 4)

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection


Tightly sealed goggles

· Body protection: Chemical resistant protective clothing

· Environmental exposure controls

Do not allow the product to contaminate the underground waters.

Do not allow the product to mix with sewage waters, ground/underground waters.

SECTION 9: Physical and chemical properties
· 9.1 Information on basic physical and chemical properties
· General Information
· Physical state

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

Undetermined.

· Flammability

Not applicable.

· Lower and upper explosion limit
· Lower:

Not determined.

· Upper:

Not determined.

· Flash point:

Not applicable.

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:
· Kinematic viscosity

Not determined.

· Dynamic:

Not determined.

· Solubility
· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure:

Not determined.

· Density and/or relative density
· Density:

Not determined.

· Relative density

Not determined.

· Vapour density

Not determined.

(Contd. on page 6)

Safety data sheet

According to Regulation (EC) No 1907/2006 (REACH) as amended by

Commission Regulation (EU) 2020/878

Printing date 29.11.2024

Version number 1

Revision: 29.11.2024

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 5)

- **9.2 Other information**
- **Appearance:**
- **Form:** Liquid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product does not present an explosion hazard.
- **Change in condition**
- **Evaporation rate** Not determined.
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Keep away from heat, open flame and ignition sources.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	50 mg/kg (ATE)
Inhalative	LC50/4 h	0.5 mg/l (ATE)

(Contd. on page 7)

Safety data sheet

According to Regulation (EC) No 1907/2006 (REACH) as amended by
 Commission Regulation (EU) 2020/878

Printing date 29.11.2024

Version number 1

Revision: 29.11.2024

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 6)

2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral	LD50	450 mg/kg (ATE)
Inhalative	LC50/4 h	0.21 mg/l (ATE)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---------------------------------------|------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | |
| · ADR, IMDG, IATA | Void |

(Contd. on page 8)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 7)

- | | |
|---|-----------------|
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
1,2-benzisothiazol-3(2H)-one
- **Hazard statements**
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
None of the ingredients is listed.

(Contd. on page 9)

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 8)

· REGULATION (EU) 2019/1148
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

· Department issuing SDS:


KGR
 KOBLENZER
 GESUNDHEITLICHE
 RISIKOBERATUNG

**KGR Kimyasal Güvenlik Riskleri
 Danışmanlık Hiz. ve Tic. Ltd. Şti.**
 İstanbul Deri OSB. Meşin Sok.

No:1 D12 Parsel
 Tuzla/ İSTANBUL
 Tel: 0 535 7247114

www.kgr.com.tr

info@kgr.com.tr

· Contact: Caner MASMANACI , Chemical Evaluation Expert
 (Turkish Standards Institute certificate no: KDU-A-0-0212)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet

According to Regulation (EC) No 1907/2006 (REACH) as amended by
 Commission Regulation (EU) 2020/878

Printing date 29.11.2024

Version number 1

Revision: 29.11.2024

Trade name: 800 STROMIT W-STOP: FIBER WATERPROOFING MATERIAL

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU