

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**
- **Product group:**  
FUGEMIT JOINT FILLERS
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** Cement based ceramic adhesive
- **Application of the substance / the mixture** Powder additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
- **WERIMIT**
- OSB 2. Kısım 24. Cad.No:18 Dösemealtı
- Antalya
- TURKEY
- 
- Phone: + 90 444 1 290
- **Further information obtainable from:** KGR - Kimyasal Güvenlik Riskleri Dan. Hiz. ve Tic. LTD. ŞTİ.
- **1.4 Emergency telephone number:** +90 444 1 290 (On weekdays, during opening times)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

EU

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Portland Cement
- **Hazard statements**  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**  
Contains Portland Cement. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

|                  |   |        |
|------------------|---|--------|
| CAS:65997-15-1   | Portland Cement   | 25-50% |
| EC no: 266-043-4 | ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335 |        |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Do not give something by mouth to the affected person.  
In case of doubt or symptoms occurring, consult to the doctor.

(Contd. on page 3)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 2)

Personal protection for the First Aider.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Immediately remove any clothing soiled with the product.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Remove contact lenses.

· **After swallowing:**

Never give to the unconscious victim anything by mouth.

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Never give anything to the unconscious person.

If swallowed, do not induce vomiting.

If swallowed or in case of vomiting, danger of entering the lungs.

In case of doubt and symptoms occurring, consult to the doctor.

Treat symptomatically.

## SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

Do not inhale combustion products.

During fire conditions, harmful gases are produced.

Can form explosive dust-air mixtures.

Dust should not be allowed to accumulate in the environment.

In case of fire, the following can be released:

Calcium oxide

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Do not inhale combustion products.

Cool endangered receptacles with water spray.

If there is a safe way to remove the containers away from the fire area, do it.

Dust concentration in the air should be kept below exposure limits.

## SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 3)

Avoid formation of dust.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid contact with eyes, skin and cloths

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

Provide suction extractors if dust is formed.

Use appropriate industrial vacuum cleaners or central vacuum systems for dust removal.

In order to eliminate the risk of explosion, prevent formation of dust on top of the surfaces.

Do not breathe the formed dust, do not let dust to contact with skin, eyes and clothing.

In case of formation of dust, take necessary precautions to prevent static electricity formation.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Do not use pressurized air to empty containers.

· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

· **Information about storage in one common storage facility:**

Do not store together with heat sources, open flame or ignition sources.

Do not store together with incompatible materials.

Store away from food material and animal feed.

Store away from dust sensitive materials.

Store away from water.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

· **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 5)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 4)

 · **Additional information:**

Exposure limit for dust:  
 3 mg/m<sup>3</sup> (respirable fraction)  
 10 mg/m<sup>3</sup> (total dust)  
 The lists valid during the making were used as basis.

 · **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.  
 · **Individual protection measures, such as personal protective equipment**

 · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes and skin.  
 Do not eat, drink, smoke or sniff while working.  
 Keep the working environment clean and tidy.  
 Ensure that eye wash stations are available at the work place.  
 Provide good ventilation.

 · **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
 Use suitable respiratory protective device in case of insufficient ventilation.

 · **Hand protection**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

 · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The gloves should comply to EN374

 · **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Penetration time > 480 min.

 · **Eye/face protection**


Tightly sealed goggles

 · **Body protection:**

Chemical resistant protective clothing  
 Antistatic shoes

EU

(Contd. on page 6)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 5)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

|   |                             |
|---|-----------------------------|
| · <b>Physical state</b>   | Solid                       |
| · <b>Colour:</b>  | Whitish                     |
| · <b>Odour:</b>   | Odourless                   |
| · <b>Odour threshold:</b>   | Not determined.             |
| · <b>Melting point/freezing point:</b>                            | Undetermined.               |
| · <b>Boiling point or initial boiling point and boiling range</b> | Undetermined.               |
| · <b>Flammability</b>   | Not determined.             |
| · <b>Lower and upper explosion limit</b>                          |                             |
| · <b>Lower:</b>   | Not determined.             |
| · <b>Upper:</b>   | Not determined.             |
| · <b>Flash point:</b>   | Not applicable.             |
| · <b>Decomposition temperature:</b>                               | Not determined.             |
| · <b>pH at 20 °C</b>  | 12                          |
| · <b>Viscosity:</b>   |                             |
| · <b>Kinematic viscosity</b>                                      | Not applicable.             |
| · <b>Dynamic:</b>   | Not applicable.             |
| · <b>Solubility</b>   |                             |
| · <b>water:</b>   | Fully miscible.<br>Soluble. |
| · <b>Partition coefficient n-octanol/water (log value)</b>        | Not determined.             |
| · <b>Vapour pressure:</b>   | Not applicable.             |
| · <b>Density and/or relative density</b>                          |                             |
| · <b>Density:</b>   | Not determined.             |
| · <b>Relative density</b>   | Not determined.             |
| · <b>Vapour density</b>   | Not applicable.             |
| · <b>Particle characteristics</b>                                 | See section 3.              |

### 9.2 Other information

|  |   |
|--|---|
| · <b>Appearance:</b>   |   |
| · <b>Form:</b>   | Powder  |
| · <b>Important information on protection of health and environment, and on safety.</b> |   |
| · <b>Ignition temperature:</b>   | Product is not selfigniting.                  |
| · <b>Explosive properties:</b>   | Product does not present an explosion hazard. |
| · <b>Change in condition</b>   |   |
| · <b>Evaporation rate</b>  | Not applicable.                               |

### Information with regard to physical hazard classes

|  |      |
|--|------|
| · <b>Explosives</b>  | Void |
| · <b>Flammable gases</b>   | Void |
| · <b>Aerosols</b>  | Void |
| · <b>Oxidising gases</b>   | Void |
| · <b>Gases under pressure</b>  | Void |
| · <b>Flammable liquids</b>   | Void |
| · <b>Flammable solids</b>  | Void |
| · <b>Self-reactive substances and mixtures</b>                                     | Void |
| · <b>Pyrophoric liquids</b>  | Void |
| · <b>Pyrophoric solids</b>   | Void |
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>   | Void |

(Contd. on page 7)

# Safety data sheet

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 6)

|                                  |      |
|----------------------------------|------|
| · <b>Oxidising solids</b>        | Void |
| · <b>Organic peroxides</b>       | Void |
| · <b>Corrosive to metals</b>     | Void |
| · <b>Desensitised explosives</b> | Void |

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Unstable in contact with acids.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Irritant gases/vapours  
Possible in traces.

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**65997-15-1 Cement, portland, chemicals**

|        |      |                      |
|--------|------|----------------------|
| Dermal | LD50 | >2000 mg/kg (rabbit) |
|--------|------|----------------------|

**9004-62-0 hecellose**

|      |      |                   |
|------|------|-------------------|
| Oral | LD50 | >2000 mg/kg (rat) |
|------|------|-------------------|

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**9004-62-0 hecellose**

|          |                                     |
|----------|-------------------------------------|
| EC50     | >1000 mg/l (bacteria)               |
| EC50/48h | >100 mg/l (daphnia)                 |
| EC50/72h | >100 mg/l (Scenedesmus subspicatus) |
| LC50/96h | >500 mg/l (danio rerio)             |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 8)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 7)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects** When reacted with large amounts of water, the pH value increases.
- **Additional ecological information:**
- **General notes:**  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

## SECTION 14: Transport information

- |   |                 |
|---|-----------------|
| · <b>14.1 UN number or ID number</b><br>· <b>ADR, IMDG, IATA</b>                            | Void            |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, IMDG, IATA</b>                           | Void            |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR, ADN, IMDG, IATA</b><br>· <b>Class</b> | Void            |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>                                     | Void            |
| · <b>14.5 Environmental hazards:</b>  | Not applicable. |
| · <b>14.6 Special precautions for user</b>  | Not applicable. |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b>                       | Not applicable. |
| · <b>UN "Model Regulation":</b>   | Void            |

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 9)



**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 8)

 · **Hazard pictograms**


GHS05 GHS07

 · **Signal word** Danger

 · **Hazard-determining components of labelling:**

Portland Cement

 · **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

 · **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

 · **Directive 2012/18/EU**

 · **Named dangerous substances - ANNEX I** None of the ingredients is listed.

 · **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

 · **REGULATION (EU) 2019/1148**

 · **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

 · **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

 · **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

 · **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

 · **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

(Contd. on page 10)

**Trade name: 250 FUGEMIT FLEX: JOINT FILLER WITH SILICONE FLEX CG2WA**

(Contd. of page 9)

**· Relevant phrases**

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.

**· Department issuing SDS:**


**KGR Kimyasal Güvenlik Riskleri  
 Danışmanlık Hiz. ve Tic. Ltd. Şti.**  
 İstanbul Deri OSB. Meşin Sok.  
 No:1 D12 Parsel  
 Tuzla/ İSTANBUL - TURKEY  
 Tel: +90 535 7247114  
[www.kgr.com.tr](http://www.kgr.com.tr)      [info@kgr.com.tr](mailto:info@kgr.com.tr)

**· Contact: Caner MASMANACI , Chemical Evaluation Expert  
 (Turkish Standards Institute certificate no: KDU-A-0-0212)**
**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Skin Sens. 1B: Skin sensitisation – Category 1B  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3